



DISCLAIMER

This document or some parts of it may not be accessible when using adaptive technology.

If you require assistance with accessing the content of the document, please contact the Planning team and quote the document name and the web page you found it on:

- email: planning.admin@ashfield.gov.uk
- telephone: 01623 457 388

Traffic Flows - 2032 Without Development, AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Mini-roundabout		Mini-roundabout appears to have unbalanced flows and may behave like a priority junction; treat results with caution. See User Guide for details.[Arms A and B have 83% of the total flow for the roundabout for one or more time segments]

Junction Network

Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Newark Rd/Kirky Folly Rd existing layout	Mini-roundabout		A, B, C	11.71	B

Junction Network Options

Driving side	Lighting	Road surface	In London
Left	Normal/unknown	Normal/unknown	

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D3	2032 Without Development	AM	ONE HOUR	07:15	08:45	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (Veh/hr)	Scaling Factor (%)
A		ONE HOUR	✓	906	100.000
B		ONE HOUR	✓	652	100.000
C		ONE HOUR	✓	303	100.000

Origin-Destination Data

Demand (Veh/hr)

	To			
		A	B	C
	A	0	743	163
	B	575	0	77
	C	161	142	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
		A	B	C
	A	0	2	3
	B	4	0	10
	C	7	10	0

Traffic Flows - 2032 Without Development, PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Mini-roundabout		Mini-roundabout appears to have unbalanced flows and may behave like a priority junction; treat results with caution. See User Guide for details.[Arms A and B have 85% of the total flow for the roundabout for one or more time segments]

Junction Network

Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Newark Rd/Kirky Folly Rd existing layout	Mini-roundabout		A, B, C	52.69	F

Junction Network Options

Driving side	Lighting	Road surface	In London
Left	Normal/unknown	Normal/unknown	

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D4	2032 Without Development	PM	ONE HOUR	16:15	17:45	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (Veh/hr)	Scaling Factor (%)
A		ONE HOUR	✓	953	100.000
B		ONE HOUR	✓	910	100.000
C		ONE HOUR	✓	322	100.000

Origin-Destination Data

Demand (Veh/hr)

	To			
		A	B	C
	A	0	783	170
	B	815	0	95
	C	190	132	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
		A	B	C
	A	0	2	3
	B	1	0	3
	C	2	3	0

Traffic Flows - 2032 With Development, AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Mini-roundabout		Mini-roundabout appears to have unbalanced flows and may behave like a priority junction; treat results with caution. See User Guide for details.[Arms A and B have 83% of the total flow for the roundabout for one or more time segments]

Junction Network

Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Newark Rd/Kirky Folly Rd existing layout	Mini-roundabout		A, B, C	13.39	B

Junction Network Options

Driving side	Lighting	Road surface	In London
Left	Normal/unknown	Normal/unknown	

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D5	2032 With Development	AM	ONE HOUR	07:15	08:45	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (Veh/hr)	Scaling Factor (%)
A		ONE HOUR	✓	962	100.000
B		ONE HOUR	✓	667	100.000
C		ONE HOUR	✓	309	100.000

Origin-Destination Data

Demand (Veh/hr)

	To			
		A	B	C
	A	0	787	175
	B	589	1	77
	C	167	142	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
		A	B	C
	A	0	2	3
	B	4	0	10
	C	6	10	0

Traffic Flows - 2032 With Development, PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Mini-roundabout		Mini-roundabout appears to have unbalanced flows and may behave like a priority junction; treat results with caution. See User Guide for details.[Arms A and B have 85% of the total flow for the roundabout for one or more time segments]

Junction Network

Junctions

Junction	Name	Junction type	Use circulating lanes	Arm order	Junction Delay (s)	Junction LOS
1	Newark Rd/Kirky Folly Rd existing layout	Mini-roundabout		A, B, C	76.55	F

Junction Network Options

Driving side	Lighting	Road surface	In London
Left	Normal/unknown	Normal/unknown	

Traffic Demand

Demand Set Details

ID	Scenario name	Time Period name	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D6	2032 With Development	PM	ONE HOUR	16:15	17:45	15	✓

Vehicle mix varies over turn	Vehicle mix varies over entry	Vehicle mix source	PCU Factor for a HV (PCU)
✓	✓	HV Percentages	2.00

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (Veh/hr)	Scaling Factor (%)
A		ONE HOUR	✓	971	100.000
B		ONE HOUR	✓	953	100.000
C		ONE HOUR	✓	333	100.000

Origin-Destination Data

Demand (Veh/hr)

	To			
		A	B	C
	A	0	797	174
	B	858	0	95
	C	201	132	0

Vehicle Mix

Heavy Vehicle Percentages

	To			
		A	B	C
	A	0	2	3
	B	0	0	3
	C	2	3	0